

GET ACCESS TO **SUCCESS**

JCB ELECTRIC SCISSOR - S2632E

Best-in-class safety



- Meets latest industry standards (EN280)
- Pothole protection, Tilt & Load sensing
- Emergency controls
- Basket lowering safety delay

Remarkable Productivity and Performance



- Fully proportional raise/ drive controls
- Waterproof platform power outlet
- Folding guard rails
- Charge level indicator

Best-in-class durability & reliability



- Full pivot boss for rigidity & durability
- Motor & component protection
- Electro Deposition Painting (EDP) process
- Wear pads to stop metal wear out

Access to Heights with Ease



- Ergonomic joystick & cradle design
- Easy foot pedal extension deck
- Battery and Hydraulic doors
- Non-marking tyres



To know more
scan here.



Watch here to
explore more.



Max. Platform Height: 7.92m | Max. Working Height: 9.92m

SPECIFICATION: ELECTRIC SCISSOR

KEY SPECIFICATIONS

Model	S2632E	
Platform size (L x W x H)	m	2.25 x 0.81 x 1.1
Load capacity	kg	250
Max. platform occupants (outdoor)	person	-
Max. platform occupants (indoor)	person	2
Max. allowable side force (indoor)	N	400
Max. allowable side force (outdoor)	N	0 - Indoor only
Max. allowable wind speed (outdoor)	m/s	0 - Indoor only
Max. allowable slope (front/back)	degrees	3
Max. allowable slope (side/side)	degrees	1.5
Ground clearance (stowed)	m	0.1
Wheelbase	m	1.85
Turning radius (outside)	m	2.1
Turning radius (inside)	m	0
Gradeability	%	25
Max driving speed (stowed)	km/h	3.4
Max driving speed (raised)	km/h	0.8
Raising time (loaded)	s	28~34
Lowering time (loaded)	s	32~38
Solid tyre dimensions	mm	380 x 125
Hydraulic oil tank vol.	L	12
Hydraulic system vol.	L	14
Hydraulic system pressure	Mpa	24.8
Battery	V	6V x 4
Power unit	V DC	24
Input voltage of Charger	V AC	100~240
Drive and steer model		2, front-wheel
Brake		2, rear-wheel
Tyres		Non-marking

DIMENSIONS

Model	S2632E	
Max. platform height	m	7.92
Max. working height	m	9.92
Extension outreach	m	0.9
Overall length (stowed)	m	2.39
Overall width (stowed)	m	0.83
Overall height (stowed, guardrail folded)	m	1.96
Overall height (stowed, guardrail unfolded)	m	2.33
Overall weight	kg	2180

INDUSTRY LEADING CUSTOMER SUPPORT



Extensive
dealer network



Trained mobile
service engineers



5 Parts
warehouses



Service vans



24x7 Support
1800-1037-386

Call us for a demo: 1800-1037-386

Follow us: [f](#) [t](#) [y](#) [i](#) [in](#) /JCBIndiaLtd



To know more
Scan the QR code

Dealer's stamp:

JCB Always looking
for a better way